## Product data sheet Characteristics

# P6B APC Essential SurgeArrest, 6 outlet





#### **Purchase**

Purchase P6B

## Overview

| Model Name           | APC Essential SurgeArrest, 6 outlet   |
|----------------------|---|
| Standard Lead Time   | Usually in Stock  |
| Product Distribution | Anguilla,Aruba,Bahamas,Barbados,Belize,Bermuda,Canada,Cayman Islands,Guyana,Haiti,Jamaica,Trinidad And Tobago,Turks And Caicos Islands,United States,VIRGIN ISLANDS (UNITED STATES) |

## Input

| Nominal Input Voltage | 120V                             |  |
|-----------------------|----------------------------------|--|
| Input Frequency       | 50/60 Hz +/- 5 Hz (auto sensing) |  |
| Input Connections     | NEMA 5-15P                       |  |
| Cord Length           | 1.83 meters                      |  |

#### Surge Protection and Filtering

| Surge energy rating | 840 |
|---------------------|-----|
| 0, 0,               |     |

#### Physical

| Maximum Height                                     | 292 mm          |
|--|-----------------|
| Maximum Width                                      | 57 mm           |
| Maximum Depth                                      | 38 mm           |
| Net Weight   | 0.45 kg         |
| Shipping Weight                                    | 0.6 kg          |
| Shipping Height                                    | 338 mm          |
| Shipping Width                                     | 147 mm          |
| Shipping Depth                                     | 38 mm           |
| Master Carton Units                                | 12.0            |
| Master Carton Dimensions (Length x Width x Height) | 16 inches       |
| Master Carton Weight                               | 18.52 lbs       |
| Color  | Charcoal        |
| SCC Codes  | 1073130421102 7 |
| Units per Pallet                                   | 288.0           |
|  |                 |

#### Environmental

| Operating Environment       | 0 - 40 °C      |
|-----------------------------|----------------|
| Operating Relative Humidity | 0 - 95         |
| Operating Elevation         | 0-3000 meters  |
| Storage Temperature         | -15 - 45 °C    |
| Storage Relative Humidity   | 0 - 95         |
| Storage Elevation           | 0-15000 meters |
|                             |                |

#### Conformance

| Regulatory Approvals        | CSA,UL 1449        |
|-----------------------------|--------------------|
| Standard Warranty           | Lifetime           |
| Equipment protection policy | Lifetime : \$25000 |

